

**40/60 Versa-Lift with 0 Counterweight Slabs**Slab Weight (lbs)
3750Number of Slabs
0Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 22100 | 24400 | 26800 | 29100 | 31400 |
| | 48 | 18500 | 20500 | 22400 | 24300 | 26300 |
| | 60 | 15900 | 17600 | 19200 | 20900 | 22600 |
| | 72 | 14000 | 15400 | 16900 | 18300 | 19800 |
| | 84 | 12400 | 13700 | 15000 | 16300 | 17600 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|--|-----|--|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 20500 | 22700 | 25000 | 27300 | 29600 |
| | 36 | 17200 | 19100 | 21000 | 22900 | 24800 |
| | 48 | 14800 | 16400 | 18100 | 19700 | 21400 |
| | 60 | 13000 | 14400 | 15900 | 17300 | 18800 |
| | 72 | 11600 | 12900 | 14100 | 15400 | 16700 |
| | 84 | 10400 | 11600 | 12800 | 13900 | 15100 |
| | 96 | 9500 | 10600 | 11600 | 12700 | 13700 |
| | 108 | 8700 | 9700 | 10700 | 11600 | 12600 |
| | 120 | 8100 | 9000 | 9900 | 10800 | 11700 |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 19100 | 21400 | 23700 | 25900 | 28200 |
| | 36 | 16000 | 18000 | 19900 | 21800 | 23700 |
| | 48 | 13800 | 15500 | 17100 | 18700 | 20400 |
| | 60 | 12100 | 13600 | 15000 | 16500 | 17900 |
| | 72 | 10800 | 12100 | 13400 | 14700 | 16000 |
| | 84 | 9800 | 10900 | 12100 | 13200 | 14400 |

***All Load Capacities are Rated with the Mast Vertical

**40/60 Versa-Lift with 1 Counterweight Slabs**Slab Weight (lbs)
3750Number of Slabs
1Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 27000 | 29900 | 32800 | 35700 | 38600 |
| | 48 | 22600 | 25000 | 27400 | 29900 | 32300 |
| | 60 | 19400 | 21500 | 23600 | 25700 | 27800 |
| | 72 | 17000 | 18900 | 20700 | 22500 | 24300 |
| | 84 | 15200 | 16800 | 18400 | 20100 | 21700 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|--|-----|--|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 25300 | 28100 | 31000 | 33800 | 36700 |
| | 36 | 21200 | 23600 | 26000 | 28400 | 30800 |
| | 48 | 18300 | 20300 | 22400 | 24400 | 26500 |
| | 60 | 16000 | 17800 | 19600 | 21500 | 23300 |
| | 72 | 14300 | 15900 | 17500 | 19100 | 20700 |
| | 84 | 12900 | 14300 | 15800 | 17300 | 18700 |
| | 96 | 11700 | 13100 | 14400 | 15700 | 17000 |
| | 108 | 10800 | 12000 | 13200 | 14400 | 15600 |
| | 120 | 10000 | 11100 | 12200 | 13300 | 14500 |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 23900 | 26800 | 29600 | 32500 | 35300 |
| | 36 | 20100 | 22500 | 24900 | 27200 | 29600 |
| | 48 | 17300 | 19300 | 21400 | 23500 | 25500 |
| | 60 | 15200 | 17000 | 18800 | 20600 | 22400 |
| | 72 | 13500 | 15100 | 16800 | 18400 | 20000 |
| | 84 | 12200 | 13700 | 15100 | 16600 | 18000 |

***All Load Capacities are Rated with the Mast Vertical

**40/60 Versa-Lift with 2 Counterweight Slabs**Slab Weight (lbs)
3750Number of Slabs
2Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 31900 | 35400 | 38900 | 42300 | 45800 |
| | 48 | 26700 | 29600 | 32500 | 35400 | 38300 |
| | 60 | 22900 | 25400 | 27900 | 30500 | 33000 |
| | 72 | 20100 | 22300 | 24500 | 26700 | 28900 |
| | 84 | 17900 | 19900 | 21800 | 23800 | 25700 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|--|-----|--|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 30100 | 33500 | 36900 | 40300 | 43800 |
| | 36 | 25200 | 28100 | 31000 | 33800 | 36700 |
| | 48 | 21700 | 24200 | 26700 | 29100 | 31600 |
| | 60 | 19100 | 21200 | 23400 | 25600 | 27800 |
| | 72 | 17000 | 18900 | 20900 | 22800 | 24800 |
| | 84 | 15300 | 17100 | 18800 | 20600 | 22300 |
| | 96 | 14000 | 15600 | 17200 | 18700 | 20300 |
| | 108 | 12800 | 14300 | 15700 | 17200 | 18700 |
| | 120 | 11900 | 13200 | 14600 | 15900 | 17300 |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 28700 | 32200 | 35600 | 39000 | 42400 |
| | 36 | 24100 | 27000 | 29800 | 32700 | 35600 |
| | 48 | 20800 | 23200 | 25700 | 28200 | 30700 |
| | 60 | 18200 | 20400 | 22600 | 24700 | 26900 |
| | 72 | 16200 | 18200 | 20100 | 22100 | 24000 |
| | 84 | 14700 | 16400 | 18200 | 19900 | 21600 |

***All Load Capacities are Rated with the Mast Vertical

**40/60 Versa-Lift with 3 Counterweight Slabs**Slab Weight (lbs)
3750Number of Slabs
3Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 36800 | 40800 | 44900 | 49000 | 53000 |
| | 48 | 30800 | 34200 | 37600 | 41000 | 44400 |
| | 60 | 26400 | 29400 | 32300 | 35200 | 38100 |
| | 72 | 23200 | 25800 | 28300 | 30900 | 33500 |
| | 84 | 20700 | 22900 | 25200 | 27500 | 29800 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|--|-----|--|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 34900 | 38900 | 42900 | 46900 | 50900 |
| | 36 | 29200 | 32600 | 36000 | 39300 | 42700 |
| | 48 | 25200 | 28100 | 31000 | 33900 | 36800 |
| | 60 | 22100 | 24700 | 27200 | 29700 | 32300 |
| | 72 | 19700 | 22000 | 24200 | 26500 | 28800 |
| | 84 | 17800 | 19800 | 21900 | 23900 | 26000 |
| | 96 | 16200 | 18100 | 19900 | 21800 | 23600 |
| | 108 | 14900 | 16600 | 18300 | 20000 | 21700 |
| | 120 | 13700 | 15300 | 16900 | 18500 | 20100 |

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 33500 | 37500 | 41500 | 45500 | 49500 |
| | 36 | 28100 | 31500 | 34800 | 38200 | 41600 |
| | 48 | 24200 | 27100 | 30000 | 32900 | 35800 |
| | 60 | 21300 | 23800 | 26400 | 28900 | 31400 |
| | 72 | 19000 | 21200 | 23500 | 25800 | 28000 |
| | 84 | 17100 | 19100 | 21200 | 23200 | 25300 |

***All Load Capacities are Rated with the Mast Vertical

**40/60 Versa-Lift with 4 Counterweight Slabs**Slab Weight (lbs)
3750Number of Slabs
4Standard Wheel Base
98

| | | Lift Capacities w/Forks Only (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Fork Face (in) | 36 | 41600 | 46300 | 51000 | 55600 | 60300 |
| | 48 | 34800 | 38700 | 42600 | 46500 | 50400 |
| | 60 | 30000 | 33300 | 36600 | 40000 | 43300 |
| | 72 | 26300 | 29200 | 32100 | 35100 | 38000 |
| | 84 | 23400 | 26000 | 28600 | 31200 | 33800 |

| | | Lift Capacities w/Boom Only (lbs) | | | | |
|--|-----|--|-------|-------|--------|--------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 39700 | 44200 | 48800 | 53400 | 58000 |
| | 36 | 33300 | 37100 | 41000 | 44800 | 48600 |
| | 48 | 28700 | 32000 | 35300 | 38600 | 41900 |
| | 60 | 25200 | 28100 | 31000 | 33900 | 36800 |
| | 72 | 22400 | 25000 | 27600 | 30200 | 32800 |
| | 84 | 20200 | 22600 | 24900 | 27200 | 29600 |
| | 96 | 18400 | 20600 | 22700 | 24800 | 26900 |
| | 108 | 16900 | 18900 | 20800 | 22800 | 24700 |
| | 120 | 15600 | 17400 | 19200 | *21000 | *21000 |

* Structural Limitations

| | | Lift Capacities w/Boom & Forks (lbs) | | | | |
|--|----|---|-------|-------|-------|-------|
| | | Counter Weight Extension (in) | | | | |
| | | 0 | 12 | 24 | 36 | 48 |
| Load Center From Boom Face (in) | 24 | 38300 | 42900 | 47500 | 52100 | 56600 |
| | 36 | 32200 | 36000 | 39800 | 43700 | 47500 |
| | 48 | 27700 | 31000 | 34300 | 37600 | 40900 |
| | 60 | 24300 | 27200 | 30100 | 33000 | 35900 |
| | 72 | 21700 | 24300 | 26900 | 29400 | 32000 |
| | 84 | 19600 | 21900 | 24200 | 26600 | 28900 |

***All Load Capacities are Rated with the Mast Vertical